

DOMESTIC HOT WATER TANKS

Hygienic, convenient and economical domestic hot water (DHW) tanks

VITOCELL 300



Domestic hot water
solutions to suit every
need

The Vitocell product line
offers horizontal, vertical,
and dual coil tanks.

VITOCELL 300

Experience Viessmann hot water technology! Comfort, convenience and reliability in one package. Available in vertical and horizontal designs, from 42 to 119 USG. Improve your domestic hot water comfort today.

Viessmann Manufacturing
Company (U.S.) Inc.
Warwick, RI 02886
(800) 288-0667
viessmann-us.com

The benefits at a glance:

- + Limited lifetime warranty available for tank and heat exchanger coil in residential applications. Please visit www.viessmann-us.com/warranty for details.
- + Convenience – Fast recovery rates ensure abundant supply of domestic hot water all day long.
- + Tank coil extends to tank bottom guaranteeing even water temperatures at all times.
- + High level of operational reliability and a long service life due to high grade stainless steel construction.
- + Extremely efficient indirect hot water production by boiler. Save up to 50% of your operating cost compared to conventional direct-fired hot water production.
- + High-performance insulation keeps standby losses and operating cost at a minimum.
- + Space-saving options: Vitocell 300-H tanks can be stacked on top of each other (92 and 119 USG sizes). Zero clearance to combustibles for all Vitocell 300 tanks.
- + Scale- and corrosion-resistant, ideal for areas with poor water quality. Completely hygienic!
- + Easy cleaning - all tanks include a 4" clean out cover for effortless access.
- + High-volume hot water – Several Vitocell 300 tanks can be combined into tank batteries.
- + All sizes now with NPT connections.

Technical Information

Model		-V (vertical)				-H (horizontal)			-B (dual-coil vertical)	
		EVIB	EVIB	EVIB	EVIB	EHA	EHA	EHA	EVBB	EVBB
Capacity	USG	42	53	79	119	53	92	119	79	119
Dimensions (inches)	Width	26	26	28	35½	25¼	32¾	35¾	28	35½
	Depth	25	25	26¼	32¾	48¾	62½	65	26¼	32¾
	Height	47	55½	68½	77	25¾	31	35	68½	77
Weight	lbs	126	143	231	187	185	379	421	249	220
Connections (MNPT)	S/R	1"	1"	1"	1"	1"	1¼"	1¼"	-	-
	Hot/Cold	¾"	¾"	1"	1"	¾"	1¼"	1¼"	1"	1¼"
	Recirc.	¾"	¾"	1"	1"	-	-	-	1"	1"
	Temp. & Relief Valves	¾"	¾"	1"	1"	1"	1"	1¼"	-	-
	Coils	-	-	-	-	-	-	-	1"	1"

Note: EVIB-119 and EVBB-119 come with soft foam wrap around insulation



Vitocell 300-H Compact
and "stackable," 119 USG
capacity



Vitocell 300-V,
42 USG capacity
Vitopearl White



Vitocell 300-V,
79 USG capacity
Vitopearl White



Vitocell 300-B, 119
USG capacity



* Models EVIB, and EVBB are only certified with AHRI according to the Performance of Indirect-Fired Water Heaters Standard.

Technical information subject to change without notice.

08/2021 Printed in USA